hp surestore magneto-optical storage family

reliable, high-volume, archival storage



hp surestore
magneto-optical jukeboxes
keep vast amounts of data
at your fingertips,
allowing you to store and
share information quickly,
safely and affordably,
year after year.



HP's vertical cable lift system combines a threepoint attachment and lowweight servo to increase the acceleration rate of the transport mechanism. The patented lift system ensures fast, reliable disk exchanges in all hp jukeboxes.



hp surestore magneto-optical jukeboxes are a safe, permanent way to archive huge amounts of information and keep it immediately accessible. A high-speed alternative to paper, tape- or microfiche-based storage, these industry-standard systems accelerate the way you store, retrieve and use your mission-critical data. With an HP jukebox, your storage system becomes a competitive asset that allows you to improve customer service, reduce back-office costs, provide information for audits, and enhance the way you analyze, share and distribute information.

built to scale

HP optical jukeboxes scale as needed. Choose your storage capacity (from 9.1 gb in the standalone drive to 2.2 tb in the hp model 2200mx); number of drives per jukebox (from 1 to 10); and number of cartridge slots (from 24 to 238). Order what you need today, and expand your system at any time. Upgrade kits allow you to add drives and cartridge slots—within the same cabinet on some models—so storage capacity can keep pace with your ever-increasing storage and performance requirements. Since all hp jukeboxes are fully compatible, you also have the option of migrating to a larger, next-generation system while leveraging your investment in disks, data, software and training.

built to perform

HP optical jukeboxes are ready to work for you. With optical cartridge capacities up to 9.1 gb, true fast-synchronous burst data transfer rates up to 10 mb/second, and sustained transfer rates of up to 6.1 mb/second, these jukeboxes increase capacity by 75 percent over earlier HP optical systems, significantly lowering the cost per gigabyte of storage.

built to last

With hp-tested robotics, drive mechanisms and media, hp optical jukeboxes are rated for up to two million MSBF* with no preventive maintenance required. Some models have hotswappable drives. If a drive ever fails, it can be replaced on the fly, without bringing the jukebox down.¹¹ And all components, including jukebox, drives and media, are backed by hp's hallmark service and support, available around the world to keep you up and running.



With two or four multifunction drives, singlebox storage capacities up to 691 gb, and 6.5-second cartridge exchange times, hp mid-range storage systems define the term "affordable power."

built for fibre

All large and medium (9.1 and 5.2 gb-based) hp jukeboxes support fibre channel connectivity through the use of hp fibre channel-to-SCSI bridge products. The increased cabling distance (up to 500 meters) provided by fibre channel allows you to physically separate your jukebox from your host server, enabling greater security without introducing the bottleneck of LAN architecture.

built for the future

HP optical jukeboxes protect your investment in key data. The systems will read every generation of industry-standard 5.25-inch magneto-optical media ever sold^{††} (including 650 mb and 1.3 gb disks), and will both read and write 2.6 gb, 5.2 gb and 9.1 gb disks.

built to work

HP optical jukeboxes are multifunctional—they support both rewritable and write-once-read-many (WORM) optical disk formats—so one system can meet your short-term and long-term storage needs. Rewritable disks allow a virtually unlimited number of writes, reads and erases with no degradation of disk or data; WORM disks allow just one write operation, and use permanently embedded codes to prevent erasure or overwriting.

* MTBF: mean time between failure. MSBF: mean swaps between failure. †† System/software dependent.

can we build one for you?

HP optical jukeboxes are more than just a fast, costeffective way to keep data accessible. They're also a competitive advantage for any company whose reputation rests with its ability to share and access information. Call your nearest HP sales office today, and see for yourself why HP is the worldwide leader in magneto-optical storage. The hp surestore 9100mx is the perfect desktop accessory for today's storage-hungry environments where virtually endless amounts of data must be stored simply, reliably, affordably and quickly.





The hp 220mx offers
70 percent more capacity
than its predecessor, the
hp 125ex. With one or two
multifunction 9.1 gb drives,
24 slots and a 12-second
cartridge exchange time, it's
a cost-effective entry to the
hp jukebox family.

technical information

hp surestore magneto-optical jukeboxes

design characteristics

model no.	2200mx	1200mx	700mx	600mx	300mx	220mx	9100mx
capacity(gb)	2165.8	1164.8	691.6	582.4	291.2	218.4	9.1
slots	238	128	76	64	32	24	1
drives	4, 6, or 10	4 or 6	2	4	2	1 or 2	1
avg. disk exchange time*	6.5 s	6.5 s	6.5 s	6.5 s	6.5 s	12 s	_
fibre channel bridge support	yes	yes	yes	yes	yes	no	no

^{*} The time it takes to stop reading data on a disk, exchange disks, and begin reading data on another disk.

drive characteristics

disk capacity	9.1 gb	
average seek	25 ms	
short seek (across 2.2 mb)	6 ms	
average latency	10 ms	
rotational speed	3000 rpm	
data transfer rate		

(software/system dependent)

reads (max. sustained) 6.1 mb/s
writes (max. sustained) 3.1 mb/s
burst (synchronous) 10 mb/s
burst (asynchronous) 4 mb/s

read/write error rate <1 per 10¹⁴ bytes

disk load/unload time

emissions

laser

load (w/spin-up) 5.5 s (avg)
unload (w/spin-down) 3.0 s (avg)
buffer size 8 mb
read buffering read aheads

write buffering immediate reporting, write re-ordering

hp 5.25-inch magneto-optical cartridges

HP magneto-optical cartridges are engineered to meet and surpass the most stringent industry standards, resulting in the highest levels of data integrity. Your operating system and software determine the type of cartridges (rewritable/write once) that are supported in your hp system. Product numbers listed below are hp's 4096 to 512 bytes/sector optical cartridges. HP jukeboxes support reads and writes on 9.1, 5.2 and 2.6 gb cartridges, and read-only on 1.3 gb and 650 mb cartridges. All cartridges are ISO/IEC 15286-compliant.

	4096 bytes/sector	2048 bytes/sector	1024 bytes/sector	512 by	tes/sector	
capacity (4.5/side)	9.1 gb (4.5/side)	8.6 gb (4.3/side)	9.1 gb (4.5/side)		9.1 gb	
single rewritable cartridge	C7983A	C7985A	C7987A	C7988	A	
single write-once cartridge	C7984A	C7986A	N/A	N/A		
dimensions						
	2200mx, 1200mx	700mx, 600mx, 300mx	220mx	9100m	ĸ	
height (3.9 in)	1806.5 mm (71.1 in)	914 mm (36.0 in)	624.7	mm (24.6 in)	100 mm	
width (6.5 in)	875.7 mm (34.5 in)	863 mm (33.9 in)	220.1	mm (8.7 in)	165 mm	
depth (11.0 in)	741.8 mm (29.2 in)	482 mm (19.0 in)	749.3	mm (29.5 in)	280 mm	
weight (net)	222.7 kg (490 lbs)	100 kg (220 lbs)	39 kg (86 lbs)	3.7 kg	(8.2 lbs)	
weight (shipping)	298.0 kg (657 lbs)	127 kg (280 lbs)	44.5 kg (98 lbs)	4.4 kg	4.4 kg (9.7 lbs)	
product certification						
	2200mx, 1200mx, 700mx, 6	500mx, 300mx, 220mx	9100mx			
safety	UL 1950, CSA 950, TUV IEC	C 950	UL 1950, CSA 950, TUV IEC 950			

FCC Class "B", CISPR 22, Class "B"

CDRH, IEC 825

FCC Class "A", CISPR 22, Class "A"

CDRH, IEC 825

[†] Results of 1/3 stroke plus latency over 50 mb bandwidth.

reliability and service

2200mx, 1200mx, 700mx, 600mx, 300mx

MSBF (robotics) 2,000,000 swaps MSBF (drive) 750,000 swaps MTBF (robotics) 100,000 hours MTBF (drive) 100,000 hours Mean Time to Repair 30 minutes preventive maintenance None required

220mx

MSBF (drive) 750,000 swaps MSBF (robotics) 1,000,000 swaps **MTBF** 100,000 hours Mean Time to Repair 30 minutes preventive maintenance None required

environmental specifications

temperature

2200mx, 1200mx

 10° to 32° C operating -40° to 60°C *non-operating gradient 10° C per hour transportation (<14 consecutive days) -30° to 60°C

700mx, 600mx, 300mx

 10° to 40° C operating *non-operating -40° to 60°C 10° C per hour gradient *transportation (<14 consecutive days) -30° to 60°C

220mx, 9100mx

operating 10° to 40°C *non-operating -40° to 60°C gradient 10° C per hour

humidity

operating 10% to 80% RH *non-operating 5% to 90% RH

shock 2200mx, 1200mx, 700mx, 600mx, 300mx

non-operating 10 cm tilt, drop test

220mx, 9100mx

non-operating 30 g trapezoidal

vibration (5 to 500 Hz)

2200mx, 1200mx, 700mx, 600mx, 300mx

operating 0.21 g rms non-operating (random) 2.1 g rms $0.5\ \overset{\circ}{g}$ (0 to peak) non-operating (swept-sine)

220mx

operating 0.21 g rms non-operating (random) 2.09 g rms 0.5 g (0 to peak) non-operating (swept-sine)

9100mx

0.3 g rms operating non-operating (random) 2.4 g rms non-operating (swept-sine) 1 g (0 to peak)

acoustic emissions

220mx

<70 dB operating ~47 dB idle

9100mx

55 dB operating

power requirements 2200mx, 1200mx

line voltage 100 to 240 VAC 50 to 60 Hz line frequency 340 W typical power consumption 560 W maximum

energy-saving mode power savings when robotics are

inactive

700mx, 600mx, 300mx 100 to 240 VAC line voltage. line frequency 50 to 60 Hz 210/240 W typical power consumption

250/275 W maximum energy-saving mode power savings when robotics are

100 to 127 VAC linevoltage (115 V) line voltage (230V) 200 to 240 VAC 50 to 60 Hz line frequency power consumption 70 W typical 100 W maximum

power savings when robotics are energy-saving mode

inactive

9100mx line voltage 100 to 240 VAC line frequency 50 to 60 Hz 30 W typical power consumption 50 W maximum

interface

220mx

2200mx, 1200mx, 700mx, 600mx, 300mx

SCSI-2

LUN converter

220mx SCSI-2 LVD

> 9100mx SCSI-2

*without media

single-ended (HD50) or

high-voltage differential (HD68)

(user-selectable)

single-ended (HD68) or low-voltage differential (HD68)

(auto-sensing)

single-ended (HD50)

a foundation to build on

HP optical jukeboxes-plus your relationship with Hewlett-Packard, the industry leader in magneto-optical storage-are the foundation of a solid, long-term storage strategy. To learn how these powerful systems can improve the effectiveness of your organization, call your nearest HP optical storage representative today.

USA 1-800-826-4111 (905) 206-4383 Canada (1) 69 82 60 60 France 0180/5 32 62 22 Germany 0990 474747



www.hp.com/go/optical

Data subject to change. © Hewlett-Packard Company 2001 5980-2479EN

